



AGIP MULTITECH

AGIP MULTITECH is a high-tec oil that meets the lubricating requirements of all devices that can be found on modern farm tractors and off-highway vehicles.

CHARACTERISTICS (TYPICAL FIGURES)

AGIP MULTITECH

SAE GRADE	10W-30		
Viscosity at 100°C	cSt	11,0	ASTM D 445
Viscosity at 40°C	cSt	88	DIN 51561
Viscosity Index	-	160	DIN ISO 2909
Flash Point	°C	228	ASTM D 92
Pour Point	°C	-33	ASTM D 97
Mass density at 15°C	kg/l	0,875	ASTM D 1298

PROPERTIES AND PERFORMANCE

The use of a special synthetic base allows AGIP MULTITECH to have a very high natural viscosity index, low pour point and appropriate viscosity characteristics throughout the whole range of operating temperatures and for all envisaged applications.

The very different lubrication needs of machineries involved have been met by a high-performance additive package, thus ensuring the product passing the performance tests set by major international bodies and manufacturers in every application.

APPLICATIONS

AGIP MULTITECH can be used in almost all devices that are normally present in farm tractors and off-highway vehicles such as gasoline and diesel (also turbo-charged type) engines, mechanical and hydrostatic transmissions, transfer case and axles, as well as transmissions with oil-immersed brakes, hydraulic systems and controls, mechanical and hydraulic power take-offs and air compressors.

SPECIFICATIONS

AGIP MULTITECH exceeds the performance requirements of the following international bodies and manufacturers:

- API SF/CE
- API CF-4
- ACEA E2
- MB 228.1
- API GL-4
- CAT TO-2
- ALLISON C-4
- FORD M2C159B
- DIN HLP
- JDM J 27
- MF M-1139, 1144, 1145
- ZF TE-ML 06B, 06C, 06D, 07B