

# AGIP ROTRA HY



AGIP ROTRA HY is an EP (Extreme Pressure) gear oil formulated for lubricating hypoid type gears operating under normal conditions for which an EP oil is required. It is also suitable for use in gear-boxes, final drives and power take-offs on farm and earth-moving machinery.

## CHARACTERISTICS (TYPICAL FIGURES)

### AGIP ROTRA HY

SAE Grade		80W-90	85W-140
Viscosity at 100°C	mm <sup>2</sup> /s	14,3	29
Viscosity at 40°C	mm <sup>2</sup> /s	130	410
Viscosity at -12°C	mPa.s	-	120000
Viscosity at -26°C	mPa.s	120000	-
Viscosity Index	-	105	98
Flash Point COC	°C	210	220
Pour Point	°C	-27	-12
Mass density at 15°C	kg/l	0,895	0,905

## PROPERTIES AND PERFORMANCE

- AGIP ROTRA HY contains special EP additives which ensure that a strong oil film is formed and maintained even under high load conditions such as occur with hypoid gears used in many automotive axles.
- Its outstanding antiwear properties, combined with its oiliness, markedly reduce wear on gear teeth and bearings.
- Its particularly good oxidation stability prevents deterioration even when in contact with components operating at high temperatures. Thus any tendency for viscosity to increase or for sludge to form is inhibited.
- It is non corrosive to steel while ensuring efficient operation of all lubricated parts.
- Its antirust properties effectively protect gears and bearings against rust. Its antifoam qualities prevent excessive formation of air bubbles which could adversely affect lubricant film continuity and corrosion even when moisture is present.

## SPECIFICATIONS

AGIP ROTRA HY meets the requirements of the following service and specifications:

- API GL-4
- US Department of the Army MIL-L-2105 level
- MAN 341 Typ N
- ZF TE-ML 01, 02A, 08, 17A
- ZF TE ML 16A, 19 (80W-90)
- VW TL 726 (level)
- LIEBHERR